

# CERTIFICATE

## of constancy of performance

### 1922 - CPR - 1909

In compliance with Regulation (EU) 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

**Road marking materials - Drop on materials - Glass beads, antiskid aggregates and mixtures of the two**  
**Glass Beads: 60-1000 µm**

(with the performance listed, see Annex I to 1922-CPR-1909 that is an inseparable part of this certificate)

placed on the market under the name or trade mark of

**TEKNO CAM SANAYİ VE TİCARET LİMİTED ŞİRKETİ**

**Çerkeşliob Mah. İmes-20 Cad. No:8 Dilovası - Kocaeli - Türkiye**

and produced in the manufacturing plant of

**TEKNO CAM SANAYİ VE TİCARET LİMİTED ŞİRKETİ**

**Çerkeşliob Mah. İmes-20 Cad. No:8 Dilovası - Kocaeli - Türkiye**

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard

**EN 1423:2012, EN 1423:2012/AC:2013**

under system 1 for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on 27.01.2023 and will remain valid until 27.01.2027 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body. The certificate is supported through annual surveillance audit and is reissued after each surveillance audit. The validity of the certificate may be confirmed in the CE register at the web address [www.dedal-bg.net](http://www.dedal-bg.net).



Attestation &  
Certification

Manager:



dipl. eng. Anna Vasileva

## ANNEX I TO CERTIFICATE OF CONSTANCY OF PERFORMANCE 1922 - CPR - 1909/21.01.2026

Performance list, acc. to EN 1423:2012, EN 1423:2012/AC:2013

Essential characteristics	Clause	Test method	Performance	
			Silan coated	Silicon coated
Visibility characteristics: - Refractive index	4.1.2.1	5.3.2.1	A	A
-Maximum weighted percentage of defective glass beads	4.1.2.2	5.3.2.2	Pass	Pass
Granulometry	4.1.3	5.3.3 (ISO 2591-1)	Pass	Pass
Dangerous substances: Arsenic (As) Lead (Pb) Antimony (Sb)	4.1.4	5.3.4	NPD	NPD
Durability: Resistance against chemicals:				
Water	4.1.5	5.3.5	Pass	Pass
Hydrochloric acid			Pass	Pass
Sodium sulphide			Pass	Pass
Calcium chloride			Pass	Pass